



HYDRAULIC COUPLINGS

K-Series ISO-A Interchange Nipple (Female Threads)

FEATURES

- Poppet style shut-off valve

CONSTRUCTION

- Machined components are manufactured using solid bar stock
- Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
- Steel componentry is plated using ROHS Compliant Trivalent Chrome.
- Steel nipples are hardened to provide heavy duty performance and resist brinelling.

AVAILABLE OPTIONS

- Contact us for all available option adders
- Oxy-Clean treatment is available

COMPATIBILITY & INTERCHANGE DATA

- Interchangeable to ISO7241 Series 'A'
- Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
- Faster ANV, Hansen HA 15000, Safeway S56-Series

SIZE	PART NUMBER	THREADS	MATERIAL	Length		Maximum OD		HEX Inch	WEIGHT Lb
				Inch	mm	Inch	mm		
1/4"	K2F1	1/8"-27 NPTF	Steel	1.22	31.0	0.87	22.1	3/4"	0.08
1/4"	K2F2	1/4"-18 NPTF	Steel	1.22	31.0	0.87	22.1	3/4"	0.07
1/4"	K2BF2	1/4"-19 BSPP	Steel	1.22	31.0	0.87	22.1	3/4"	0.07
1/4"	K2OF2	7/16"-20 ORB	Steel	1.22	31.0	0.87	22.1	3/4"	0.08
3/8"	K3F3	3/8"-18 NPTF	Steel	1.70	43.2	0.97	24.6	7/8"	0.11
3/8"	K3BF3	3/8"-19 BSPP	Steel	1.70	43.2	0.97	24.6	7/8"	0.11
3/8"	K3OF3	9/16"-18 ORB	Steel	1.70	43.2	0.97	24.6	7/8"	0.13
1/2"	K4F4	1/2"-14 NPTF	Steel	1.77	45.0	1.23	31.2	1 1/16"	0.21
1/2"	K4BF4	1/2"-14 BSPP	Steel	1.77	45.0	1.23	31.2	1 1/16"	0.21
1/2"	K4OF4	3/4"-16 ORB	Steel	1.77	45.0	1.23	31.2	1 1/16"	0.22
1/2"	K4OF5	7/8"-14 ORB	Steel	1.77	45.0	1.23	31.2	1 1/16"	0.21
1/2"	K4F6	3/4"-14 NPTF	Steel	1.77	45.0	1.37	34.8	1 3/16"	0.33
1/2"	K4BF6	3/4"-14 BSPP	Steel	1.77	45.0	1.37	34.8	1 3/16"	0.33



WARNING: Cancer and Reproductive Harm