

## BV-40FD150/300



### Features :

- Two-piece split body design.
- Investment casting.
- Blow-out proof stem.
- Floating ball.
- Full bore and RF flanged end.
- ISO5211 direct mounting.

### Application :

- General application.
- Water, oil, gas and steam.
- Light chemical.

### 2-Pcs Flanged Ball Valve, Full Bore, ANSI 150# / 300# RF End

Size	: 1/2" - 8" (DN15 - DN200)
Body	: CF8M / CF8 / WCB
Ball & Stem	: SS 316 / SS 304
Seat	: TFM-1600
End Standard	: 150# / 300# RF Flanged
Pressure Rating	: 150 psi / 300 psi
Temperature Range	: 0 - 200 C

## BV-40FD10K/20K



### Features :

- Two-piece split body design.
- Investment casting.
- Blow-out proof stem.
- Floating ball.
- Full bore and RF flanged end.
- ISO5211 direct mounting.

### Application :

- General application.
- Water, oil, gas and steam.
- Light chemical.

### 2-Pcs Flanged Ball Valve, Full Bore, JIS 10K / 20K RF End

Size	: 1/2" - 8" (DN15 - DN200)
Body	: SCS14 / SCS13 / SCPH2
Ball & Stem	: SS 316 / SS 304
Seat	: TFM-1600
End Standard	: JIS 10K / 20K RF Flanged
Pressure Rating	: 10 bar / 20 bar
Temperature Range	: 0 - 200 C

## BV-40FDPN16/40



### Features :

- Two-piece split body design.
- Investment casting.
- Blow-out proof stem.
- Floating ball.
- Full bore and RF flanged end.
- ISO5211 direct mounting.

### Application :

- General application.
- Water, oil, gas and steam.
- Light chemical.

### 2-Pcs Flanged Ball Valve, Full Bore, DIN PN16 / PN40 RF End

Size	: 1/2" - 8" (DN15 - DN200)
Body	: 1.4408 / 1.4308 / 1.0619
Ball & Stem	: SS 316 / SS 304
Seat	: TFM-1600
End Standard	: PN16 / PN40 RF Flanged
Pressure Rating	: 10 bar / 40 bar
Temperature Range	: 0 - 200 C

## BV-50FD150/300(T/L)



### Features :

- Three-way ball valve.
- Investment casting.
- Type T-port or type L-port.
- Floating ball.
- Full bore and RF flanged end.
- ISO5211 direct mounting.

### Application :

- General application.
- Water, oil, gas and steam.
- Light chemical.

### 3-way Flanged Ball Valve, Full Bore, ANSI 150# / 300# RF End

Size	: 1/2" - 4" (DN15 - DN100)
Body	: CF8M / CF8 / WCB
Ball & Stem	: SS 316 / SS 304
Seat	: TFM-1600
End Standard	: 150# / 300# RF Flanged
Pressure Rating	: 150 psi / 300 psi
Temperature Range	: 0 - 200 C

## BV-50FD10K/20K(T/L)



### Features :

- Three-way ball valve.
- Investment casting.
- Type T or type L.
- Floating ball.
- Full bore and RF flanged end.
- ISO5211 direct mounting.

### Application :

- General application.
- Water, oil, gas and steam.
- Light chemical.

### 3-way Flanged Ball Valve, Full Bore, JIS 10K / 20K RF End

Size	: 1/2" - 4" (DN15 - DN100)
Body	: SCS14 / SCS13 / SCPH2
Ball & Stem	: SS 316 / SS 304
Seat	: TFM-1600
End Standard	: JIS 10K / 20K RF Flanged
Pressure Rating	: 10 bar / 20 bar
Temperature Range	: 0 - 200 C

## BV-50FDPN16/40



### Features :

- Three-way ball valve.
- Investment casting.
- Type T or type L.
- Floating ball.
- Full bore and RF flanged end.
- ISO5211 direct mounting.

### Application :

- General application.
- Water, oil, gas and steam.
- Light chemical.

### 3-way Flanged Ball Valve, Full Bore, DIN PN16 / PN40 RF End

Size	: 1/2" - 4" (DN15 - DN100)
Body	: 1.4408 / 1.4308 / 1.0619
Ball & Stem	: SS 316 / SS 304
Seat	: TFM-1600
End Standard	: PN16 / PN40 RF Flanged
Pressure Rating	: 10 bar / 40 bar
Temperature Range	: 0 - 200 C