

# Pneumatic Actuator Valve

## BV-20D-PD / BV-20D-PS



### Features :

- Two-Piece body design.
- ISO5211 direct mounting.
- Full bore.
- BSPT or NPT standard.
- Double acting / Single acting.
- Accessories available.

### Application :

- General application.
- Food and beverages systems.
- Water treatment systems.

### Pneumatic 2-pcs Ball Valve, Threaded End, Double / Single Acting

Size	: 1/4" - 3" (DN8 - DN80)
Body	: CF8M / CF8 / WCB
Ball & Stem	: SS316 / SS304
Seat	: TFM-1600 / PTFE
End Standard	: Threaded End
Pressure Rating	: 1000 psi
Temperature Range	: 0 -200 C

## BV-30D-PD / BV-30D-PS



### Features :

- Three-Piece body design.
- ISO5211 direct mounting.
- Full bore.
- BSPT or NPT standard.
- Double acting / Single acting.
- Accessories available.

### Application :

- General application.
- Food and beverages systems.
- Water treatment systems.

### Pneumatic 3-pcs Ball Valve, Threaded End, Double / Single Acting

Size	: 1/4" - 4" (DN8 - DN100)
Body	: CF8M / CF8 / WCB
Ball & Stem	: SS316 / SS304
Seat	: TFM-1600 / PTFE
End Standard	: Threaded End
Pressure Rating	: 1000 psi
Temperature Range	: 0 -200 C

## BV-20FD-PD / BV-40FD-PS



### Features :

- Two-piece split body design.
- ISO5211 direct mounting.
- Full bore and RF flanged end.
- Floating ball.
- Double acting / Single acting.
- Accessories available.

### Application :

- General application.
- Food and beverages systems.
- Water treatment systems.

### Pneumatic Ball Valve, RF Flanged End, Double / Single Acting

Size	: 1/2" - 8" (DN15 - DN200)
Body	: CF8M / CF8 / WCB
Ball & Stem	: SS316 / SS304
Seat	: TFM-1600 / PTFE
End Standard	: ANSI 150# / ANSI 300#
Pressure Rating	: 150 psi / 300 psi
Temperature Range	: 0 - 200 C

## BFV-700-PD / BF-700-PS



### Features :

- Light weight & compact design.
- Tight shut-off for liquid and gas.
- Seat replaceable.
- Various seat & disc material.
- Double acting / Single acting.
- Accessories available.

### Application :

- Hot & cold water systems.
- Powder & cement.
- Water treatment systems.

### Pneumatic Butterfly Valve, Wafer End, Double / Single Acting

Size	: 1-1/2" - 24" (DN40 - DN600)
Body	: GG-25 / GGG50 / GSC-25N
Disc & Stem	: CF8 / CF8M / ALBC2 & SS410
Seat	: EPDM / NBR / Viton
End Standard	: Wafer 10K, 150#, PN10/PN16
Pressure Rating	: 10 bar
Temperature Range	: 0 - 130 C

## Pneumatic Plastic Ball Valve



### Features :

- Light weight & compact design.
- UPVC, CPVC, PVDF, PP body.
- Double union type.
- Socket, threaded and flanged.
- Double acting / Single acting.
- Accessories available.

### Application :

- General application.
- Food and beverages systems.
- Water treatment systems.

### Pneumatic Plastic Ball Valve, Double / Single Acting

Size	: 1/2" - 4" (DN15 - DN100)
Body	: UPVC / CPVC / PVDF / PP
Disc & Stem	: UPVC / CPVC / PVDF / PP
Seat	: PTFE
End Standard	: Socket, threaded and flanged.
Pressure Rating	: 10 bar
Temperature Range	: 0 - 120 C

## Pneumatic Sanitary Butterfly Valve



### Features :

- Light weight & compact design.
- Various body, disc & seat material.
- Seat replaceable.
- Tri-Clamp and welded type.
- Double acting / Single acting.
- Accessories available.

### Application :

- Food and beverages systems.
- Pharmaceutical.
- Water treatment systems.

### Pneumatic Sanitary Butterfly Valve, Double / Single Acting

Size	: 1" - 8" (DN25 - DN200)
Body	: SS316 / SS304
Disc & Stem	: SS316 / SS304
Seat	: EPDM / Silicone
End Standard	: Tri-Clamp / Welded
Pressure Rating	: 10 bar
Temperature Range	: 0 - 120 C